PRODUCT DATA SHEET

Z-Cam PanTilt 3388

Pan-and-tilt pipe inspection camera

The Z-Cam PanTilt 3388 is a professional pipe inspection camera with a 28 mm pan-and-tilt camera head. The head rotates through 360 degrees and tilts through 180 degrees for detailed inspection of lateral connections, joint defects and hidden cracks. Its 60 m Ø 8 mm push rod, 10-inch display, recording to an SD card or USB drive and the meter counter support fully documented on-site inspections.



KEY ADVANTAGES

360-degree pan head
Full circumferential view

180-degree tilt head
For lateral details

60 m push rod
Ø 8 mm fibreglass cable

Self-leveling camera head
Standard equipment

512 Hz transmitter
Standard equipment

RECOMMENDED APPLICATIONS

Lateral connections	360-degree rotation and 180-degree tilt enable detailed circumferential inspection.
Pipe condition surveys	Inspection of joint defects, cracks and damage in 40-200 mm pipes.
Documented inspections	On-site images and video can be recorded to an SD card or USB drive.

SYSTEM EQUIPMENT

Camera head: Ø28 mm, 360-degree rotation and 180-degree tilt
Push rod: Ø 8 mm fibreglass cable, 60 m
Standard equipment: self-leveling head, 512 Hz transmitter and meter counter
Documentation: 10-inch LCD, recording to an SD card or USB drive

TECHNICAL SPECIFICATION

Detailed technical data

Feature	Specification
Camera head	Ø28 mm
Rotation and tilt	360-degree rotation, 180-degree tilt
Push rod	Ø 8 mm fibreglass cable - 60 m
Recommended pipe diameter	40-200 mm
90-degree pipe fitting	Minimum Ø100 mm
Waterproofing	IP68, 2 bar / 20 m water depth
Built-in transmitter	Standard equipment, 512 Hz
Self-leveling head	Standard equipment
Meter counter	Standard equipment
Display	10-inch LCD
Recording media	16 GB SD card or USB drive
Menu languages	English, German, French, Italian, Spanish, Portuguese, Russian, Dutch
Battery life	5 hours
Weight	23 kg

SERVICE AND SUPPORT

HU
Hungarian service
Fast local support

1 YEAR
Warranty
Hungarian service support

TEL
Expert support
+36 70 591 2610

IMPORTANT NOTE

The 28 mm camera head rotates through 360 degrees and tilts through 180 degrees. It can pass through 90-degree pipe fittings from a minimum pipe diameter of Ø100 mm. The camera head is rated IP68 and 2 bar for operation at water depths up to 20 metres.

Further information and ordering

shop.zsalugepkft.hu

info@zsalugepkft.hu | +36 70 591 2610